

UBIIK MIMOMAX TORNADO

400-430MHz Radio Spec Sheet



The Ubiik Mimomax Tornado is a full-duplex, software flexible, ultra spectrally efficient, long range point-to-multipoint base or remote radio unit with built-in intelligent network features for Critical Network Infrastructure. With scalable data rates and an efficient random access protocol, it can provide near real-time access to a large number of remote sites with very high reliability and low latency. The Ubiik Mimomax Tornado is fully compatible with all Ubiik Mimomax products and provides economical SCADA and Telemetry solutions to remote sites in the Power, Gas and Water acquisition and distribution industries.

KEY FEATURES

- ▶ *Point-to-Point, Point-to-Multipoint*
- ▶ *Linux Applications Engine*
- ▶ *Ultra Spectrally Efficient*
- ▶ *Scalable Data Throughput Rates*
- ▶ *SCADA, Telemetry & Data Solutions*
- ▶ *Software Flexible & Intelligent*
- ▶ *Very Low Latency*
- ▶ *Very Low Power Consumption*
- ▶ *Full-duplex*
- ▶ *Capacity to Simultaneously Operate in Poll and Interrupt Modes*
- ▶ *UHF Licensed Spectrum*
- ▶ *Ethernet, Serial & USB Interface*
- ▶ *IP Data Encryption & Firewall Security*
- ▶ *Advance Software Features*
- ▶ *User Settable Frequency*
- ▶ *User Programmable Power*
- ▶ *Indoor & Outdoor Mountable*



400-430MHz UBIIK MIMOMAX TORNADO SPECIFICATIONS

General			Duplexer (Internal)						
Gross Data Rates (Full Duplex)	50 kHz	320/640/960/1280kb/s (AU/NZ/EU)	Type	Bandpass					
	25 kHz	144/289/434/579kb/s (USA)	Tx / Rx Split	5 MHz minimum					
		160/320/480/640kb/s (AU, NZ, EU, CAN)	Frequency Range	400 to 430 MHz					
Configuration	12.5 kHz	80/160/240/320kb/s (USA/CAN)	Duplexer Sub Bands	400-430 MHz					
Supply Voltage	10.5v DC to 60V DC			Stop Band Attenuation >60 dB @ >5 MHz from centre					
Maximum Power Consumption	26W (at 13.8V)								
Standby Power Consumption	20W typical			Pass Band Bandwidth ⁽⁶⁾ 1 MHz					
Ambient Temperature Range	-30°C (-40°C) ⁽¹⁾ to +60°C (+70°C) ⁽²⁾								
Mounting	1U High Rack Mount								
	Pole Mount								
	Wall Mount								
	DIN Rail Mount								
Dimensions (L x W x H)	173 x 266 x 43mm								
Receiver									
Modulation	QPSK/16/64/256QAM			Type Bandpass					
Number of MIMO receivers	2								
Symbol Rate	2x40k symbols/sec (50 kHz)			Tx / Rx Split 4.5 MHz					
	2x20k (AU,NZ,EU,CAN), 2x18.1k (USA) symbols/sec (25kHz)			Frequency Range 400 to 430 MHz					
	2x10k symbols/sec (12.5kHz)			Insertion Loss <1.75 dB					
Modulation ⁽³⁾ Sensitivity ⁽⁴⁾ for 10-4 BER	50kHz	<-109.5/-103/-97/-91dBm		Stop Band Attenuation >70 dB					
	25kHz	<-112.5/-106/-100/-93.5dBm		Pass Band Bandwidth ⁽⁶⁾ 2 MHz					
	12.5kHz	<-115.5/-109/-104/-96dBm		Mounting 2U High Rack Mount					
Modulation ⁽³⁾ Sensitivity ⁽⁴⁾ for 10-6 BER	50kHz	<-108.5/-102/-96/-89.5dBm							
	25kHz	<-111.5/-105/-99/-92dBm							
	12.5kHz	<-114.5/-108/-102/-94.5dBm							
Measurements via duplexer at antenna port									
Frequency Range	400 to 430 MHz other frequencies available on request			Interfaces (Digital & Analogue)					
Frequency Step Size	5 kHz & 6.25 kHz selectable								
Frequency Accuracy and Stability	better than +/- 1ppm			ETHERNET Dual 10BaseT/100BaseT					
Nominal Channel Bandwidth	12.5 kHz, 25 kHz, 50kHz								
Transmitter									
Number of MIMO transmitters	2			Connectors 2 x RJ45					
Modulation	QPSK/16/64/256QAM			ASYNCHRONOUS SERIAL (Other data interfaces available via external media converters ⁽⁷⁾)					
Symbol Rate	2x40k symbols/sec (50kHz)			Format Dual RS232					
	2x20k (AU,NZ,EU,CAN), 2x18.1k (USA) symbols/sec (25kHz)			Connectors 2 x RJ45					
	2x10k symbols/sec (12.5kHz)			Baud Rate 300 - 115,200 baud					
RF Power Output ⁽⁵⁾	Avg. before duplexer 2 x 27dBm			USB High speed USB 2.0					
	Avg. after duplexer 2 x 24dBm			Connectors Type A and mini B					
	Peak before duplexer 2 x 35dBm			ALARM 1 set of volt-free change over contacts					
RF Power Control Range	>20 dB			GPIO Analogue/Digital 4 x s/w configurable I/O ports					
Frequency Range	400 to 430 MHz			FREQUENCY REFERENCE Input/Output isolated differential pair					
Frequency Step Size	5 kHz & 6.25 kHz selectable								
Compliances									
Radio Performance	AS/NZS 4768.3:2018 ⁽⁸⁾			EMC EN 301 489					
	FCC 47CFR part 90								
	IC Canada			EN 301 489-1 V1.9.2 (2011-09) EN301 489-4 V2.1.1 (2012-11)					
	RSS-119								
	ETSI EN 302-561 V2.1.1 (2016-03) ⁽⁸⁾			FCC 47CFR part 15					
EMC	EN 301 489			Environmental 60950-22 Outdoor Safety ⁽⁹⁾					
	EN 301 489-1 V1.9.2 (2011-09) EN301 489-4 V2.1.1 (2012-11)								
Environmental	Safety IEC 60950-1: 2005, Am 1 : 2009								
Important: Specifications are subject to change without prior notice									
(1) -40°C for continuous operation. (2) +70°C for RRU-T with 25% duty cycle. (3) Systems employing modulation swapping will automatically reduce the modulation order at a signal level higher than the specified sensitivity level. (4) Sensitivity as specified includes forward error correction and internal duplexer loss. (5) Tornado RF output remains constant at all modulations. (6) The maximum acceptable frequency shift without retuning the duplexer is also subject to the stop band performance. (7) Contact Ubiik for more information (8) Tested up to receiver modulation of 64 QAM and transmitter modulation of 256 QAM for 25kHz and 50kHz channel (9) Designed to meet									