

## UBIIK MIMOMAX TORNADO X

### 900MHz Radio Spec Sheet



Tornado X is a high Tx power addition to our full duplex, MIMO product range. Offering a Tx power which remains stable across all modulations, full compatibility with the Tornado radio allows for a mix of radios in the network to suit terrain or meet network requirements.

Software flexible, ultra-spectrally efficient and offering extremely low latency to provide near real-time communications and visibility across critical infrastructure.

Tornado X is ideally suited as:

- a base radio for coverage limited multipoint systems or networks where traffic is uplink predominant
- a point-to-point linking radio for longer links and obstructed paths.

Available in 900MHz and in 12.5kHz, 25kHz, 50kHz, 75kHz, 100kHz, 150kHz or 200kHz channel sizes.

#### KEY FEATURES

- *Point-to-Point, Point-to-Multipoint*
- *Linux Applications Engine*
- *Ultra Spectrally Efficient*
- *Scalable Data Throughput Rates*
- *SCADA, Telemetry & Data Solutions*
- *Software Flexible & Intelligent*
- *Very Low Latency*
- *Very Low Power Consumption*
- *Full-duplex*
- *Capacity to Simultaneously Operate in Poll and Interrupt Modes*
- *900MHz Licensed Spectrum*
- *Ethernet, Serial & USB Interface*
- *IP Data Encryption & Firewall Security*
- *Advance Software Features*
- *User Settable Frequency*
- *User Programmable Power*
- *Indoor & Outdoor Mountable*

# 900MHz UBIIK MIMOMAX TORNADO X SPECIFICATIONS

General			Transmitter			
Gross Aggregate Data Rates	200 kHz	1333/2667/4000/5333kbps Full-duplex	Number of MIMO transmitters	2		
	150 kHz	985/1969/2954/3938kbps Full-duplex	Modulation	QPSK/16/64/256QAM		
	100 kHz	655/1309/1964/2618kbps Full-duplex	Symbol Rate	2x166.667k symbols/sec (200 kHz)		
	75 kHz	480/960/1440/1920kbps Full-duplex		2x123.077k symbols/sec (150 kHz)		
	50 kHz	320/640/960/1280kbps Full-duplex		2x81.818k symbols/sec (100 kHz)		
	25 kHz	160/320/480/640kbps Full-duplex		2x60k symbols/sec (75 kHz)		
Part 101 and ISED RSS-119)	12.5 kHz (FCC Part 24)	80/160/240/320kbps Full-duplex		2x40k symbols/sec (50 kHz)		
	12.5 kHz (FCC Part 24)	71/143/214/286kbps Full-duplex		2x18.576k symbols/sec (25kHz)		
Configuration	2 x 2 Full Duplex MIMO 10.5v DC			2x10k symbols/sec (12.5kHz) (FCC Part 101 and ISED RSS-119)		
Supply Voltage	to 60V DC			2x8.929k symbols/sec (12.5kHz)(FCC Part 24)		
Maximum Power Consumption (100% duty cycle)	73.5W (at 13.8V)		RF Power Output <sup>(5)</sup>	Avg. before duplexer 2x36dBm		
	67.5W typical			Avg. after duplexer 2x34dBm		
Standby Power Consumption	<7.75W typical			Peak before duplexer 2x44dBm		
				Peak after duplexer 2x42dBm		
Ambient Temperature Range	-30°C (-40°C) <sup>(1)</sup> to +60°C (+70°C) <sup>(2)</sup>		RF Power Control Range	>20 dB		
Mounting	1U High Rack Mount		Frequency Range	896-960 MHz		
Dimensions (L x W x H)	330 x 480 x 45mm		Frequency Step Size	5 kHz & 6.25 kHz selectable		
Weight	6 kg radio unit only, excl. mounts		Frequency Accuracy and Stability	better than +/- 1ppm		
Receiver			Duplexer (Internal)			
Modulation	QPSK/16/64/256QAM		Type	Bandpass		
Number of MIMO receivers	2		Tx / Rx Split	9 MHz		
Symbol Rate	2x166.667k symbols/sec (200 kHz)		Frequency Range	896-960 MHz other frequencies available on request		
	2x123.077k symbols/sec (150 kHz)		Stop Band Attenuation	>70 dB		
	2x81.818k symbols/sec (100 kHz)		Pass Band Bandwidth <sup>(6)</sup>	1 MHz		
	2x60k symbols/sec (75 kHz)					
	2x40k symbols/sec (50 kHz)					
	2x18.576k symbols/sec (25kHz)					
	2x10k symbols/sec (12.5kHz)(FCC Part 101 and ISED RSS-119)					
	2x8.929k symbols/sec (12.5kHz)(FCC Part 24)					
Modulation <sup>(3)</sup> Sensitivity <sup>(4)</sup> for 10 <sup>-4</sup> BER	200 kHz	<-105/-97/-91/-85dBm	Type	Bandpass		
	150 kHz	<-106/-99/-92/-86dBm	Tx / Rx Split	3.6 MHz minimum		
	100 kHz	<-107/-100/-93/-88dBm	Frequency Range	806 to 960 MHz		
	75 kHz	<-107/-102/-94/-89dBm	Insertion Loss	<1.5 dB		
	50 kHz	<-109.5/-103/-97/-91dBm	Stop Band Attenuation	>70 dB		
	25 kHz	<-112.5/-106/-100/-93.5dBm	Pass Band Bandwidth <sup>(6)</sup>	2 MHz		
	12.5 kHz	<-115.5/-109/-103/-96dBm	Mounting	To be confirmed		
Modulation <sup>(3)</sup> Sensitivity <sup>(4)</sup> for 10 <sup>-6</sup> BER	200 kHz	<-103/-96/-90/-83dBm				
	150 kHz	<-105/-97/-91/-84dBm				
	100 kHz	<-106/-99/-92/-86dBm				
	75 kHz	<-107/-100/-93/-87dBm				
	50 kHz	<-108.5/-102/-96/-89.5dBm				
	25 kHz	<-111.5/-105/-99/-92dBm				
	12.5 kHz	<-114.5/-108/-102/-94.5dBm				
Measurements via duplexer at antenna port						
Frequency Range	896-960 MHz other frequencies available on request					
Frequency Step Size	5 kHz & 6.25 kHz selectable					
Frequency Accuracy and Stability	better than +/- 1ppm					
Compliances			Interfaces (Digital & Analogue)			
Radio Performance	US: FCC 47CFR part 101 (pending) and part 24 Canada: IC RSS-119 pending		ETHERNET	Dual 10BaseT/100BaseT		
EMC	US: FCC 47CFR part 15 Canada: IC RSS-GEN		Connectors	2 x RJ45		
Safety	IEC 62368-1: 2014 + A11: 2017		ASYNCHRONOUS SERIAL	(Other data interfaces available via external media converters <sup>(7)</sup> )		
			Format	Dual RS232		
			Connectors	2 x RJ45		
			Baud Rate	300 - 115,200 baud		
			USB	High speed USB 2.0		
			Connectors	Type A		
			ALARM	1 set of volt-free change over contacts		
			GPIO Analogue/Digital	4 x s/w configurable I/O ports		
			FREQUENCY REFERENCE Input/ Output	isolated differential pair		
Important: Specifications are subject to change without prior notice						
<p>(1) -40°C for continuous operation.          (2) +70°C for RFU-T with 25% duty cycle.          (3) Systems employing modulation swapping will automatically reduce the modulation order at a signal level higher than the specified sensitivity level.          (4) Sensitivity as specified includes forward error correction and internal duplexer loss.          (5) Tornado RF output remains constant at all modulations.          (6) The maximum acceptable frequency shift without retuning the duplexer is also subject to the stop band performance.          (7) Available via external media converter.</p>						